

YSP-1, 2 Type Disc Steam Trap(Pipeline)

As a disc type trap, it effectively uses the difference in the thermodynamic characteristics between steam and condensate. It is appropriate for places where there is a high possibility of freezing damages, including where the outlet or a steam main is exposed to the atmosphere.

03



YSP-1 Type



YSP-2 Type

Features

- Economical Trap (YSP-1 : no need for a separate bypass pipeline & simple handle operation blows foreign substances out and discharges condensed water.)
- No air binding during the start-up & easy repair.
- Easy installation in a pipeline : compact product & either the screwed type or flanged type can be used according to installation conditions.

Specification

Type	YSP-1, YSP-2	
Applicable pressure	0,034~1,2MPa	
Fluid temperature	220°C below	
End connection	KS PT SCREW	
Materials	Body	GC200
	Disc, seat	STS
Hydraulic test pressure	1,8MPa	


▶ Install a strainer (80 MESH or more) at the front end when installing the valve.

Dimensions


(mm)

Type	Size	L	H1	H2	Weight (kg)
YSP-1 Type	15(½")	120	33	95	2,2
	20(¾")	125	33	95	2,2
	25(1")	135	37	97	2,8
YSP-2 Type	15(½")	80	33	84	1,6
	20(¾")	84	33	84	1,6
	25(1")	88	37	87	2,2

Dimensional drawing



Type YSP-1
(Bypass valve attached)



Type YSP-2

Flow curve

